

cl
said one end of said stay-on tab being adapted to push downwardly on a portion of said can cover surrounded by said scoring means when another end of said stay-on tab is pulled upwardly, said score means defining a content take-out hole, said support being connected to a central portion of said stay-on tab, said central portion extending contiguously to said one end of said stay-on tab, said central portion having an edge spaced from said another end of said stay-on tab such that said another end can be pulled upwardly from said upper surface of said can cover while said central portion remains juxtaposed in close contact with said upper surface of said can cover, said another end of said stay-on tab being a planar member, each of said one end and said another end being inclined upwardly from said upper surface such that when one of the ends of said stay-on tab is pressed downwardly another end of said stay-on tab moves upwardly away from said upper surface of said can cover, said can cover being configured so as to be stackable upon identical can cover.

12. (Replacing previous Claim 8) The apparatus of Claim 11, said support having an elliptical or polygonal cross-section so as to prevent said stay-on tab from being rotated.

13. (Replacing previous Claim 9) The apparatus of Claim 7, further comprising:
an auxiliary support protruding upwardly from said upper surface of said can cover, said auxiliary support positioned beside said support, said auxiliary support connected to said central portion of said stay-on tab, said auxiliary support passing through said central portion and protruding upwardly from said central portion.

14. (Replacing previous Claim 10) The apparatus of Claim 13, said auxiliary support having an upper end spread so as to form a head.